

IN THE CLAIMS

1. (currently amended) A wireless communication system for data transmission by radio waves between a data supply source apparatus and a data provided destination apparatus, in which:

the data supply source apparatus is operable photograph a moving image or a still image and to perform an RFID (Radio Frequency Identification) tag function that transmits image data obtained from a photographing operation by a back scattering scheme by absorbing or reflecting external radio waves provided by the data provided destination apparatus in accordance with a bit string of the data through an on/off control of an antenna switch to make an antenna in a terminated state or an open state; and

the data provided destination apparatus is operable to perform a reader function that transmits the radio waves in a predetermined frequency band and reads data of an RFID tag in accordance with reflected waves from the data supply source apparatus which represent the image data obtained from the photographing operation.

2. (previously presented) The wireless communication system recited in claim 1, in which:

the data provided destination apparatus transmits a non-modulated carrier or a modulated control signal, and the data supply source apparatus transmits data by absorbing or reflecting the external radio waves on a basis of termination control of the antenna; and

the data provided destination apparatus receives the data on a basis of presence/absence of the reflected waves from the supply source apparatus.

3. (previously presented) The wireless communication system recited in claim 1, in which:

the data provided destination apparatus has means for storing or reproducing data received from the data supply source apparatus.

4. (previously presented) The wireless communication system recited in claim 1, in which:

the data provided destination apparatus receives the data on a basis of presence/absence of the reflected waves from the supply source apparatus, performs error detection, and transmits an error detection result in a form of a control signal made of an ASK, PSK or FSK modulation wave, and the data supply source apparatus demodulates the control signal at a reception unit and demodulation unit to perform re-transmission control.

5. (previously presented) The wireless communication system recited in claim 1, in which:

the data supply source apparatus having photographing means is remotely controlled by a command in a control signal transmitted from the data provided destination apparatus.

6-10. (canceled)

11. (new) The wireless communication system recited in claim 1, in which the data supply source apparatus is a digital camera or a mobile phone.

12. (new) The wireless communication system recited in claim 1, in which the data provided destination apparatus is a personal computer, a television, or a printer.

13. (new) The wireless communication system recited in claim 1, in which the image data is transmitted by the data supply source apparatus at a frequency of approximately 2.4 GHz.

14. (new) The wireless communication system recited in claim 1, in which the data provided destination apparatus includes a circuit to provide confirmation to the data supply source apparatus whether the image data supplied from the data supply source apparatus is correct or incorrect.